





THE LARGEST STRAIGHT TRUCKS.

Turn to the next generation in the industry's most trusted diesel truck refrigeration unit.



PERFORMANCE SPECIFICATIONS



Supra* S10 Unit. Confidently transport perishable and frozen food via the largest sized trucks with the Supra S10 unit. With exceptional capacity, airflow and overall performance all wrapped in a new sleek design, it's the perfect way to add value to fleets of all sizes.

Quality Engineering. By streamlining the design and using fewer mechanical components, we've extended the service interval to 2,000 hours, increased the overall lifespan and greatly reduced total operating costs.

Intelligent Operation. The APXTM control system – as seen on the Carrier Transicold $X4^{TM}$ and VectorTM platforms – provides the ideal balance of temperature control, fuel management and remarkable control intelligence to maintain an ideal environment inside the truck.

Expert Service and Support. With 180 dealer locations across North America and 24/7 service access, help is never out of reach.

Condenser Dimensions

75.4" x 32.1" x 24.2" (1,914 x 815 x 615 mm)

Evaporator Dimensions

48.2" x 23.5" x 13" (1,225 x 597 x 330 mm)

Body Opening

49.0" x 13.8" (1,245 x 351 mm)

Approximate Weight

TDB-5B: 1,025 lb (466 kg) without standby TDS-5B: 1,102 lb (501 kg) with electric standby

Evaporator Airflow

1,600 cfm (2,718 m³/hr)

Cooling Capacity

Evaporator Return Air Temp.	Diesel Operation		Standby Operation	
	BTU/hr	Watts	BTU/hr	Watts
35°F (2°C) 0°F (-18°C) -20°F (-29°C)	37,000 23,000 15,000	10,850 6,740 4,400	27,000 21,000 14,000	7,915 6,155 4,105

Ambient at 100°F (38°C) Speed: 2,100 rpm diesel/60Hz electric standby operation

Standard Features Include:

Tier 4 Final D1105 smart diesel engine, 3 cylinder Electronic controls High-power 150-amp alternator ESI (Extended Service Interval) package 2,000-hour service interval

Multistage, synthetic media oil filter Water-separating fuel filter

Heavy-duty, low-noise dry air cleaner Extended-life coolant

05K24, 4-cylinder compressor 24.4 in³ displacement

Refrigerant R-404A, 8.2 lb (3.7 kg)

High-efficiency refrigeration system

Electronic suction modulation valve Brazed plate heat exchanger

Automatic start/stop fuel saver

Three-way refrigeration valve system

High-efficiency microchannel condenser Maintenance-free electric condenser fans

Maintenance-free evaporator fan motors Automatic hot-gas heating system

APX control system

Data recorder

Automated pretrip with componentlevel fault detection

On-board diagnostics with visual indicator and audible alarm

Setpoint and operating mode locking

Smart door switch logic

Programmable FreshProtect perishable protection system

City speed control (quieter operation)

Standard Features (continued):

Automatic defrost control Cab Command™ Controller

Intuitive controls

Digital readout

Setpoint/operating mode

Supply air temperature

Ambient temperature

Hour meters (switch on, diesel,

standby, maintenance)

Top grille

Bottom panel

Installation package

Accessories and Options:

Carrier eSolutions™ telematics DataTrak™

Electric standby:

208/230v-3ph-60Hz

or 460v-3ph-60Hz

Battery box (separate from truck)

30-gallon fuel tank (center fill or end fill)

50-gallon fuel tank

Remote temperature sensor

Open door shutdown switch

Fuel sensor

Stealth™ Noise Reduction

Auxiliary heat systems

Fuel heater

Remote light bar

Snow/rain cover

Refrigerant R-452A, 8.2 lb (3.7 kg)

Oil drain adapter

Specifications are subject to change without notice.

Warranty: Product warranty and limitations are outlined in Form 62-12102.

This warranty is applicable only in North America. Consult your Carrier Transicold representative for warranty coverage elsewhere. Form: 62-12200. Rev A.

North America

Carrier Transicold 700 Olympic Drive Athens, GA 30601 USA **Central America and Mexico** Carrier Transicold Ejercito Nacional 253-A Piso 5

Ejercito Nacional 253-A Piso 5 Colonia Anahuac 11320 Mexico D.F.

©2021 Carrier. All Rights Reserved. Printed in USA 07/21. Carrier, Transicold and Supra are registered trademarks of Carrier Corporation.

